



I-Beam Order Form



Name _____ PO# _____

Company Name _____

Billing Address _____

Shipping Address _____

Is shipping address (circle one) _____ residential / _____ commercial / _____ job site

Phone () _____ Email _____ Fax () _____

How to figure Door size

We will figure everything out for you as far as room for adjustment, ride height, and pre-drill framing
 (circle one) New construction Existing Remodel

Height from bottom of grade board to bottom of door opening header _____

Height from top of concrete floor to bottom of door header _____

Height of where you want bottom of door in relation to bottom of grade board (typically same height as bottom of wall metal) _____

Existing door; Height of where door slides at base to bottom of track, tight measurement _____

Recommend 2x8 through opening for facemount track and 2x6 through opening with top mount track flush with bottom of header

Door widths are standard nominal dimension 6'; 8'; 10'; 12'; 14'; 15'; 16', 18'; 20'; 24'; 30'. Cut charge \$50 per door to cut

Ideal Door opening needs to be 5" overall narrower than door panel width; 4" to 8" lap will work but not ideal. Example 30' door is 29'7" opening

Door opening width _____

Door Size Width x Height Single or Split 100 or E Series	Qty.	Latch Options Standard Handle included Keyed /Stainless + \$\$	Track Options Top Mount(logo) Face Mount	NOTES Steel / Post Frame Job Name/ PO EzGlide Rollers / Bearing w/ J-channel

Email to info@ibeamdoor.com Call 815-945-3667 Fax 815-945-7073