

## **I-Beam Order Form**



## (ONLY ONE DOOR PER ORDER)

Name:			PO#
Company Name:			
Billing Address (City,State, Zip):			
Shipping Address (City,State, Zip):			
Shipping Address is (Circle one): Res	dential / Commercial / Job Site		
Phone: ()	Email:	F	ax:
	How to figure I ps tack board 1", above base of imensions out for clearance, adj 3-6 weeks):	grade board 2", below concreustments, ride height and pre-	-drill framing.
s this a (circle one): New Constr	uction Existing Remodel		
Height from bottom of grade bo	ard to bottom of door opening	header:	
Height of where you want botton (Bottom of door is typically 2-3" ab		of grade board:	
Existing door; height of where of the control of th			
Door Opening Width:			
Split Door Center Guide (Circle	one): Stub Post Concrete	Anchor	
Job Date (When you need the de	oor by):		
What series of door (E-Series o	r 100-Series):		<del>.</del>
Recommend 2x8 through opening Door widths are standard nominal			nt Track flush with top o track boards s \$50 per door to cut
deal door opening width for split o Example: 30' door is 29'7" opening			work but isn't ideal.
Door Size	Latch Ontions	Track Ontions	Notes

Door Size Width X Height Single or Split	Latch Options Standard Handle Included Keyed/Stainless (extra)	Track Options Top Mount (2x6 board) Face Mount (2x8 board) Track board size	Notes Steel/Post Frame Name/PO EzGlide Rollers or Bearing with J-Channel